



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
31.01.2001 Bulletin 2001/05

(51) Int. Cl.<sup>7</sup>: **C07D 301/12**

(21) Application number: **00202658.1**

(22) Date of filing: **24.07.2000**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(30) Priority: **27.07.1999 IT MI991658**

(71) Applicant: **Enichem S.p.A.**  
**20097 S. Donato Milanese (Milano) (IT)**

(72) Inventors:  
• **Paparatto, Giuseppe**  
**20092 Cinisello Balsamo, Milan (IT)**  
• **Forlin, Anna**  
**35010 Vigonza, Padova (IT)**  
• **Tegon, Paolo**  
**30030 Oriago, Venezia (IT)**

(74) Representative:  
**De Gregori, Antonella**  
**Ing. Barzano & Zanardo Milano S.p.A.**  
**Via Borgonuovo 10**  
**20121 Milano (IT)**

(54) **Process for the preparation of Epoxides**

(57) A continuous process is described for the preparation of olefin oxides by direct epoxidation of an olefin with hydrogen peroxide, or compounds capable of producing hydrogen peroxide under the reaction conditions, in a solvent medium, in the presence of a catalytic system consisting of a zeolite containing titanium and a buffer system with a pH controlled within the values of 5.5 to 8.0, consisting of a nitrogenated base and a salt thereof with an organic or inorganic acid.

The process allows high conversions and selectivities of the olefin into the corresponding oxide with a catalytic activity stable over a period of time.

## Description

[0001] The present invention relates to a continuous process for the preparation of epoxides.

[0002] More specifically, the present invention relates to a continuous process for the preparation of propylene oxide by direct epoxidation of propylene with hydrogen peroxide, or compounds capable of producing hydrogen peroxide under the reaction conditions, in a solvent medium, in the presence of a catalytic system consisting of a zeolite containing titanium and a buffer system with a pH controlled within values of 5.5 to 8.0, consisting of a nitrogenated base and a salt thereof with an organic or inorganic acid.

[0003] Epoxides, or olefin oxides, are intermediates useful for the preparation of a wide variety of compounds. For example epoxides can be used for the production of glycols, condensation polymers such as polyesters, or for the preparation of intermediates useful in the synthesis of polyurethane foams, elastomers, seals and similar products.

[0004] The use of zeolitic compounds with an MFI structure containing titanium atoms (TS-1) as catalysts in the direct epoxidation reactions of olefin compounds with hydrogen peroxide, is known in literature (EP-100,119).

[0005] However, the acidity which characterizes these catalysts contributes, together with the possible acidity present in the homogeneous phase, to catalyzing consecutive solvolytic reactions on the epoxide with the opening of the ring. This leads to an increase in production costs for both the decrease in yield to epoxide and for the separation of the by-products formed.

[0006] To overcome these disadvantages, processes have been proposed in the art for improving the catalytic performances of these zeolitic compounds by appropriate activation treatment.

[0007] For example, the patent EP-230,949 describes an epoxidation process which uses, as catalyst, a titanium silicalite treated, before or during the epoxidation reaction, with a neutralizing agent selected from organic derivatives of silicon of the type  $X-Si(R)_3$  or hydrosoluble substances deriving from cations of group I and II with a different base strength.

[0008] The patent EP-712,852 relates to an epoxidation process of olefins in the presence of titanium-silicalite which uses as neutralizing agent a non base salt selected from lithium chloride, sodium nitrate, potassium sulfate and ammonium phosphate. Under these conditions the maximum selectivity obtained is in the order of 93%.

[0009] The patent U.S. 5,675,026 describes an epoxidation process which uses as catalyst a titanium-silicalite treated, before or during the reaction, with a neutral or acid salt, selected from  $Na_2SO_4$ ,  $(NH_4)_2SO_4$ ,  $NH_4NO_3$  or  $NaH_2PO_4$ .

[0010] Operating according to these known processes, propylene oxide is obtained with a good yield and selectivity.

[0011] These processes, however, have disadvantages deriving from the fact that these catalytic systems have a short duration of the catalytic cycle and consequently require frequent regeneration.

[0012] This creates considerable problems from both a technical and economic point of view, above all when the epoxidation process is carried out in continuous.

[0013] In fact, a lowering in the production yield of the epoxide and a reduction in the catalytic activity during the subsequent regeneration phases, have been observed.

[0014] It has now been found that it is possible to overcome the disadvantages of the known art described above by means of the process of the present invention, which is based on the use of a buffer system with a pH controlled within the values of 5.5 and 8.0 and which is such that the pH of the reaction system ranges within the above values.


[0015] The use of this buffer system has substantial advantages, and in particular:

(i) it allows the catalytic activity to be kept stable over a period of time, reducing the frequency of the regeneration cycles of the catalyst to the minimum; and

(ii) it allows the preparation of epoxides with high yields and selectivities.

[0016] In accordance with this, the present invention relates to a continuous process for the preparation of epoxides by direct oxidation of an olefin with hydrogen peroxide, or compounds capable of producing hydrogen peroxide under the reaction conditions, in a solvent medium, in the presence of a catalytic system consisting of a synthetic zeolite containing titanium atoms and a buffer system with a pH controlled within the values of 5.5 and 8.0, consisting of a nitrogenated base and a salt thereof with an organic or inorganic acid.

[0017] The nitrogenated base is selected from compounds having general formula (I)



wherein: R, R<sub>1</sub> and R<sub>2</sub>, the same or different, can be H, an alkyl group with C<sub>1</sub>-C<sub>10</sub> carbon atoms, a -COR<sub>3</sub> group wherein R<sub>3</sub> is an alkyl group with C<sub>1</sub>-C<sub>10</sub> carbon atoms or NH<sub>2</sub>, or a



group wherein n is a number from 1 to 10 and R<sub>4</sub> and R<sub>5</sub> are H or C<sub>1</sub>-C<sub>10</sub> alkyl groups.

[0018] Preferred compounds having formula (I) are: ammonia, methylamine, ethylamine, diethylamine, trimethylamine, ethanolamine, diethanolamine, triethanolamine, n-propylamine.

[0019] Organic acids which can be used for the purposes of the present invention can be selected from carboxylic acids, such as acetic acid, formic acid, propionic or butyric acid and their derivatives, such as for example oxyacids such as glycol acid and α-lactic acid.

[0020] The inorganic acids are selected from sulfuric and phosphoric acid.

[0021] Sulfuric acid, acetic acid and formic acid are particularly preferred for the purposes of the present invention.

[0022] The olefin compounds which can be used in the process of the present invention can be selected from organic compounds having at least one double bond and can be linear or branched aliphatic, aromatic, alkylaromatic and cyclic. They are preferably olefin hydrocarbons having from 2 to 30 carbon atoms in the molecule and containing at least one double bond.

[0023] Examples of olefins suitable for the purposes of the present invention are selected from those having general formula (II)



wherein: R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub> and R<sub>4</sub>, the same or different, can be H, an alkyl radical with from 1 to 20 carbon atoms, an aryl radical, an alkylaryl radical with from 7 to 20 carbon atoms, a cycloalkyl radical with from 6 to 10 carbon atoms, an alkylcycloalkyl radical with from 7 to 20 carbon atoms. The radicals R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub> and R<sub>4</sub>, can form, in pairs, saturated or unsaturated rings. These radicals may additionally contain halogen atoms, nitro, nitrile, sulfonic groups and relative esters, carbonyl, hydroxyl, carboxyl, thiol, amine and ether groups.

[0024] Examples of olefins which can be epoxidated with the process of the present invention are: ethylene, propylene, allyl chloride, allyl alcohol, butenes, pentenes, hexenes, octeneheptenes-1, 1-tridecene, mesityl oxide, isoprene, cyclo-octene, cyclohexene or bicyclic compounds such as norbornenes, pinenes, etc. The olefins can carry the above substituents both on the unsaturated carbon atoms and on different positions.

[0025] The oxidizing agent used in the process of the present invention is hydrogen peroxide (H<sub>2</sub>O<sub>2</sub>) or a compound which is capable of generating H<sub>2</sub>O<sub>2</sub> under the epoxidation conditions.

[0026] An aqueous solution of hydrogen peroxide is preferably used, at a minimum concentration of 1% by weight,

preferably with a titer greater than or equal to 35% by weight.

[0027] The quantity of hydrogen peroxide with respect to the olefin is not critical, but a molar ratio olefin/H<sub>2</sub>O<sub>2</sub> ranging from 10:1 to 1:10, preferably from 6:1 to 1:2, is preferably used.

[0028] The epoxidation reaction can be carried out in one or more solvents liquid at the epoxidation temperatures. Solvents of a polar nature are typically used, such as alcohols (methanol, ethanol, isopropyl alcohol, t-butyl alcohol, cyclohexanol), hydro-alcohol mixtures, ketones (for example acetone, methyl ethyl ketone, acetophenone), ethers (tetrahydrofuran, butyl ether), aliphatic and aromatic hydrocarbons, halogenated hydrocarbons, esters.

[0029] Methanol and, among the ketones, acetone, are preferably used. A mixture of methanol/water with a weight ratio ranging from 50/50 to 99/1, is particularly preferred.


[0030] The catalyst which can be used in the process of the present invention is selected from those generally known by the name of titanium-silicalites.

[0031] For example titanium-silicalites with an MFI structure can be used, described in the patent U.S. 4,410,501 which also specifies their structural characteristics.

[0032] Titanium-silicalites can also be used, in which part of the titanium is substituted by other metals, such as boron, aluminum, iron or gallium. These substituted titanium silicalites and the methods for their preparation are described in European patent applications 226,257, 226,258 and 266,825.

[0033] It is also possible to use titanium silicalites with a MEL or intermediate MFI/MEL structure described in Belgian patent 1,001,038. Other titanium-silicalites can be selected from beta zeolites containing titanium and having a BEA structure, described in Spanish patent 2,037,596, ZSM-12 containing titanium and optionally aluminum, described in "Journal of Chemical Communications, 1992, page 745).

[0034] The preferred catalyst according to the present invention is titanium-silicalite having the general formula:



wherein: x represents a number ranging from 0.0001 to 0.04, the value of x preferably ranging from 0.01 to 0.025, and described, for example, in U.S. patents 4,410,501, 4,824,976, 4,666,692, 4,656,016, 4,859,785, 4,937,216.

[0035] The quantity of catalyst used in the process of the present invention is not critical; it is selected however in such a way as to allow the epoxidation reaction to be completed in the shortest time possible.

[0036] The quantity of catalyst is generally selected in relation to various parameters, such as the reaction temperature, the reactivity and concentration of the olefins, the concentration of hydrogen peroxide, the type and composition of the solvent, the catalytic activity and type of reactor or reaction system used.

[0037] The quantity of catalyst typically ranges from 1 to 15% by weight with respect to the reaction mixture, preferably from 4 to 10% by weight.

[0038] The catalyst can be used in the form of powder, pellets, microspheres, extruded product or other convenient physical forms.

[0039] The temperature used in the process of the present invention generally ranges from 20 to 150°C, preferably from 40 to 100°C. The operating pressure is that which allows the olefin to be maintained in liquid phase at the preset reaction temperature. The operating pressure is generally higher than atmospheric pressure when gaseous olefins are used.

[0040] The epoxidation process of the present invention can be carried out in batch, semi-continuous or, preferably, in continuous.

[0041] Various types of reactor can be used in the process of the present invention, for example a slurry reactor or a fixed-bed reactor.

[0042] The epoxidation process is preferably carried out in continuous, by feeding into a reaction zone containing the catalyst: hydrogen peroxide, the solvent, preferably methanol/water, propylene and an aqueous buffer solution having the composition and pH defined above, so that the pH is controlled in the reactor within values ranging from 5.5 to 8.0, preferably within values ranging from 6 and 7.0.

[0043] Conversion refers to the quantity of hydrogen peroxide which reacts during the epoxidation reaction with respect to the quantity charged into the reactor.

[0044] Selectivity refers to the number of moles of epoxide produced per moles of reacted hydrogen peroxide.

[0045] The epoxidation product obtained with the process of the present invention is separated and recovered from the reaction mixture using conventional techniques such as fractionated distillation.

[0046] The following examples have the sole purpose of describing the present invention in greater detail and should in no way be considered as limiting its scope.

Example 1 (comparative)Oxidation of propylene

5 [0047] The epoxidation reaction is carried out in a stirred, 1.5 litre, AISI 316L steel reactor, equipped with a thermostat-regulation system, level control, pressure control and filter for continuously removing the solution, maintaining the catalyst in the reactor.

[0048] 760 g of a solution of methanol/water (93/7) and 40 g of titanium silicalite TS-1 (EniChem, with a titanium content equal to 2.05% by weight) are initially charged. After thermostat-regulating the system at 50°C and pressurizing  
10 with propylene to 12 bar, the following products are then fed in continuous by means of pumps:

1. 1970 g/hour of a solution of methanol/water 92.8/7.2 by weight
2. 230 g/hour of an aqueous solution of H<sub>2</sub>O<sub>2</sub> at 35% by weight
3. propylene
- 15 4. 100 g/hour of water.

[0049] The overall reaction mixture in the feeding (without propylene) is equal to 2300 g/hour and its composition is the following:

H<sub>2</sub>O<sub>2</sub> 3.5%, H<sub>2</sub>O 17%, MeOH 79.5%.

20 The pressure in the reactor is maintained at 12 bar, feeding propylene.

[0050] The reaction trend is followed by taking samples every two hours and determining the residual H<sub>2</sub>O<sub>2</sub> by titration with sodium thiosulfate and the reaction products by gaschromatography. The pH of the reaction mixture is determined on the liquid effluent leaving the reactor after partially degassing the propylene.

[0051] The results are shown in table 1.

25

Table 1

Time (hrs)	H <sub>2</sub> O <sub>2</sub> conversion %	PO selectivity %	Reaction pH
6	94	65	4.5
16	88	78	4.5
30	85	85	4.5

30

35 Example 2 (comparative)

[0052] The reaction is carried out under the same conditions as example 1, but using a reaction temperature equal to 60°C.

The results are indicated in table 2.

40

Table 2

Time (hrs)	H <sub>2</sub> O <sub>2</sub> conversion %	PO selectivity %	Reaction pH
6	90	67	4.5
16	82	75	4.5
30	75	80	4.5

45

50 Example 3

[0053] The reaction is carried out as described in example 2, but feeding in continuous (100 g/hour) an aqueous buffer solution containing 0.048% of NH<sub>3</sub> and 0.12% of (NH<sub>4</sub>)<sub>2</sub>SO<sub>4</sub> instead of water. The results are shown in table 3.

55

Table 3

Reaction hours	H <sub>2</sub> O <sub>2</sub> conversion %	PO selectivity %	Reaction pH
16	97	96.8	6.1
30	96	97.2	6.0
60	94	97.6	6.1
100	94	98.1	5.9

Example 4

[0054] The same procedure is adopted as in example 2, but feeding (100 g/hour) an aqueous buffer solution containing 0.048% of NH<sub>3</sub> and 0.12% of ammonium acetate (CH<sub>3</sub>COONH<sub>4</sub>).

[0055] The results are shown in table 4.

Table 4

Reaction Hours	H <sub>2</sub> O <sub>2</sub> conversion %	PO selectivity %	Reaction pH
16	97	96.2	6.5
60	95.5	97.8	6.5
100	94.8	98.1	6.4
300	95.1	98.5	6.5

Example 5

[0056] The same procedure is adopted as in example 2, but feeding (100 g/hour) an aqueous buffer solution containing 0.048% of NH<sub>3</sub> and 0.10% of ammonium formiate (HCOONH<sub>4</sub>).

[0057] The results are shown in table 5.

Table 5

Time (hours)	H <sub>2</sub> O <sub>2</sub> conversion %	PO selectivity %	Reaction pH
16	98.0	96.2	6.4
60	96.2	96.8	6.3
100	95.2	97.2	6.3
400	95.1	98.0	6.3
600	95.0	98.1	6.3

[0058] From the data indicated in tables 3, 4 and 5, high conversion and selectivity values are observed together with a stability in the catalyst activity.

Example 6 (comparative)

[0059] The same procedure is adopted as in example 2, but feeding (100 g/hour) an aqueous solution containing 0.10% of sodium acetate. The results are shown in table 6.

Table 6

Time (hours)	H <sub>2</sub> O <sub>2</sub> conversion %	PO selectivity %	Reaction pH
6	96	84	5.8
16	94	91	6.0
30	87	96	6.2
60	75	95	6.0

[0060] From the values indicated in the table, a deterioration in the catalyst over a period of time, is observed.

#### 15 Example 7 (comparative)

[0061] The same procedure is adopted as in example 2, but feeding 100 g/hour of an aqueous solution containing 0.10% of NaNO<sub>3</sub>. The results are shown in table 7.

Table 7

Time (hrs)	H <sub>2</sub> O <sub>2</sub> conversion %	PO selectivity %	Reaction pH
6	92	71	4.5
16	87	82	4.4
30	84	86	4.5

#### Example 8 (comparative)

[0062] The same procedure is adopted as in example 2, but feeding 100 g/hour of an aqueous solution containing 0.04% of NaOH. The results are shown in table 8.

Table 8

Time (hrs)	H <sub>2</sub> O <sub>2</sub> conversion %	PO selectivity %	Reaction pH
6	85	93	6.6
16	65	98	7.3

#### Example 9 (comparative)

[0063] The same procedure is adopted as in example 2, but feeding 100 g/hour of an aqueous solution containing 0.2% of NaCl. The results are shown in table 9.

Table 9


Time (hrs)	H <sub>2</sub> O <sub>2</sub> conversion %	PO selectivity %	Reaction pH
6	90	78	4.5
16	85	84	4.5

#### 55 Claims


1. A continuous process for the preparation of olefin oxides by the direct epoxidation of an olefin with hydrogen peroxide, or compounds capable of producing hydrogen peroxide under the reaction conditions, in a solvent medium,

in the presence of a catalytic system consisting of a zeolite containing titanium atoms and a buffer system with a pH controlled within values ranging from 5.5 to 8.0, consisting of a nitrogenated base and a salt thereof with an organic or inorganic acid.

- 5 2. The process according to claim 1, wherein the nitrogenated base is selected from compounds having general formula (I)




wherein: R, R<sub>1</sub> and R<sub>2</sub>, the same or different, can be H, an alkyl group with C<sub>1</sub>-C<sub>10</sub> carbon atoms, a -COR<sub>3</sub> group wherein R<sub>3</sub> is an alkyl group with C<sub>1</sub>-C<sub>10</sub> carbon atoms or NH<sub>2</sub>, or a



group, wherein n is a number ranging from 1 to 10 and R<sub>4</sub> and R<sub>5</sub> are H or C<sub>1</sub>-C<sub>10</sub> alkyl groups.

- 30 3. The process according to claim 2, wherein the nitrogenated base is selected from ammonia, methylamine, ethylamine, dimethylamine, trimethylamine, ethanolamine, diethanolamine, triethanolamine, n-propylamine.
4. The process according to claim 1, wherein the organic acids can be selected from carboxylic acids, such as acetic acid, formic, propionic and butyric acid or their derivatives such as glycolic acid and α-lactic acid.
- 35 5. The process according to claim 1, wherein the inorganic acids are selected from sulfuric acid and phosphoric acid.
6. The process according to claim 1, wherein the olefin compounds can be selected from organic compounds having at least one double bond and can be linear or branched aliphatic, aromatic, alkylaromatic and cyclic.
- 40 7. The process according to claim 6, wherein the olefin compounds are selected from olefin hydrocarbons having from 2 to 30 carbon atoms in the molecule and containing at least one double bond.
8. The process according to claim 7, wherein the olefin compounds are selected from those having general formula (II)
- 45 (II)



wherein: R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub> and R<sub>4</sub>, the same or different, can be H, an alkyl radical with from 1 to 20 carbon atoms, an aryl radical, an alkylaryl radical with from 7 to 20 carbon atoms, a cycloalkyl radical with from 6 to 10 carbon atoms, an alkylcycloalkyl radical with from 7 to 20 carbon atoms.



9. The process according to claim 8, wherein the radicals R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub> and R<sub>4</sub> can form, in pairs, saturated or unsaturated rings.
10. The process according to claim 8, wherein the radicals R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub> and R<sub>4</sub> can contain substituents selected from halogens, nitro, nitrile, sulfonic groups and relative esters, carbonyl, hydroxyl, carboxyl, thiol amine and ether groups.
11. The process according to claim 1, wherein the olefin is propylene.
12. The process according to claim 1, wherein the hydrogen peroxide is used as an aqueous solution with a minimum titer of 1% by weight.
13. The process according to claim 12, wherein the hydrogen peroxide is used as an aqueous solution with a titer equal to or higher than 35% by weight.
14. The process according claim 1, wherein the molar ratio between olefin and hydrogen peroxide ranges from 10/1 to 1/10.
15. The process according claim 14, wherein the molar ratio between olefin and hydrogen peroxide ranges from 6/1 to 1/2.
16. The process according to claim 1, wherein the catalyst is selected from titanium silicalites having general formula (III):
$$x\text{TiO}_2 \cdot (1-x)\text{SiO}_2$$
wherein: x ranges from 0.0001 to 0.04.
17. The process according to claim 16, wherein the value of x ranges from 0.01 to 0.025
18. The process according to claim 16, wherein in the titanium silicalite part of the titanium is substituted by metals selected from boron, aluminum, iron or gallium.
19. The process according to claim 1, wherein the solvent medium is selected from alcohols, hydro-alcohol mixtures, ketones, ethers, aliphatic and aromatic hydrocarbons, halogenated hydrocarbons, esters or glycols.
20. The process according to claim 19, wherein the alcohols are selected from methanol, ethanol, isopropyl alcohol, t-butyl alcohol, cyclohexanol.
21. The process according to claim 20, wherein the ketones are selected from acetone, methyl ethyl ketone, acetophenone.
22. The process according to claim 19, wherein the ethers are selected from tetrahydrofuran and butyl ether.
23. The process according to claim 19, wherein the solvent medium is a mixture of methanol/water with a weight ratio ranging from 50/50 and 99/1.
24. The process according to claim 1, wherein the epoxidation reaction is carried out at a temperature ranging from 20 to 150°C.
25. The process according to claim 24, wherein the temperature ranges from 40 to 100°C.



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 00 20 2658

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 591 875 A (CHANG T ET AL) 7 January 1997 (1997-01-07) * the whole document, particularly paragraph bridging columns 4 and 5, and column 5, line 60, to column 6, line 14 *	1-25	C07D301/12
P, X	WO 99 48882 A (SOLVAY (SOCIETE ANONYME)) 30 September 1999 (1999-09-30) * the whole document *	1-25	
D, Y	EP 0 712 852 A (ARCO CHEMICAL TECHNOLOGY, L.P.) 22 May 1996 (1996-05-22) * the whole document, particularly page 4, lines 18-40 *	1	
D, A	EP 0 757 043 A (DEGUSSA AKTIENGESSELLSCHAFT) 5 February 1997 (1997-02-05) * the whole document *	1	
P, Y	WO 00 17178 A (ARCO CHEMICAL TECHNOLOGY L.P. ET AL) 30 March 2000 (2000-03-30) * the whole document *	1-25	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
P, Y	DATABASE WPI Section Ch, Week 200007 Derwent Publications Ltd., London, GB; Class E13, AN 2000-075359 XP002151674 & JP 11 309378 A (ASAHI KASEI KOGYO KK ET AL), 9 November 1999 (1999-11-09) * abstract *	1-25	C07D
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 1 November 2000	Examiner Allard, M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 20 2658

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-11-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5591875 A	07-01-1997	CA 2182434 A	03-02-1997
		CN 1149053 A	07-05-1997
		EP 0757045 A	05-02-1997
		JP 9118672 A	06-05-1997
		RU 2140415 C	27-10-1999
		SG 42429 A	15-08-1997
WO 9948882 A	30-09-1999	BE 1011851 A	01-02-2000
		AU 3035999 A	18-10-1999
EP 712852 A	22-05-1996	US 5646314 A	08-07-1997
		CA 2162410 A	17-05-1996
		CN 1131152 A	18-09-1996
		JP 8225556 A	03-09-1996
EP 757043 A	05-02-1997	DE 19528219 A	06-02-1997
		BR 9603245 A	28-04-1998
		CA 2182436 A	02-02-1997
		CN 1147510 A	16-04-1997
		JP 9118671 A	06-05-1997
		KR 189031 B	01-06-1999
		SG 42428 A	15-08-1997
		US 5675026 A	07-10-1997
WO 0017178 A	30-03-2000	US 6037484 A	14-03-2000
		AU 6193299 A	10-04-2000
JP 11309378 A	09-11-1999	NONE	

EPO FORM P4439

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82